

Serial No. 10/002,746

In the Claims

Please substitute the following claims for those currently on file in the application:

1. (Currently Amended) A method for transmitting channel quality information in a wireless communication system comprising at least one base station and at least one mobile station, the method comprising:

varying a rate for reporting channel quality information from a mobile station to a base station as a function of the presence or absence of a reception of a data transmission at the mobile station, wherein the mobile station reports channel quality information at a first rate in the absence of a reception of a data transmission from the base station and, upon detection of a reception of a data transmission from the base station, the mobile station reports channel quality information at a second rate for a prescribed duration.

2. (Canceled)

3. (Canceled)

4. (Currently Amended) The method according to claim 1, ~~wherein the mobile station reports channel quality information at a first rate in the absence of a reception of a transmission from the base station and,~~ upon detection of a reception of a data transmission from the base station, the mobile station reports channel quality information at a plurality of rates over a prescribed time period after detection of the reception of a data transmission, wherein the plurality of rates are different than the first rate.

5. (Currently Amended) The method according to claim 4, wherein the prescribed time period includes a plurality of time intervals such that the channel quality information is reported at different ones of the plurality of rates during different ones of the plurality of time intervals.

6. (Currently Amended) The method according to claim ~~2~~ 1, wherein the second rate is faster than the first rate.

7. (Currently Amended) The method according to claim ~~6~~ 1, further comprising the step of estimating channel quality at the base station while the mobile station is reporting at the second rate, wherein estimated channel quality is used to derive a transmission format for a subsequent transmission.

Serial No. 10/002,746

8. (Original) The method according to claim 7, wherein the transmission format includes one or more parameters selected from the group consisting of modulation format, number of codes, and transmission rate.

9. (Currently Amended) The method according to claim 6 1, further comprising the step of estimating channel quality at the base station while the mobile station is reporting at the second rate, wherein estimated channel quality is used to calculate an amount of redundancy needed for a retransmission of a previous data transmission.

b 10. (Original) The method according to claim 1, wherein the channel quality information comprises a transmission rate calculated by the mobile station based on one or more channel conditions.

11. (Currently Amended) A method for adapting the rate of reporting channel quality information in a wireless communication system including at least one base station and at least one mobile station, the method comprising:

reporting channel quality information from the at least one mobile station to the at least one base station at a first rate in the absence of a reception of a data transmission at the at least one mobile station; and

in the presence of a reception of a data transmission at the at least one mobile station, adapting the rate for reporting channel quality information from the at least one mobile station to the at least one base station from the first rate to a second rate for a prescribed duration.

12. (Original) The method according to claim 11, wherein the second rate is faster than the first rate.

13. (Original) A method for transmitting channel quality information in a wireless communication system including at least one base station and at least one mobile station, the method comprising:

varying a rate for reporting channel quality information from a mobile station to a base station as a function of the number of base stations that the mobile station is communicating with.

Serial No. 10/002,746

14. (Original) The method according to claim 13, wherein the mobile station reports channel quality information at a first rate when the mobile station is communicating with one base station and wherein the mobile station reports channel quality information at a second rate when the mobile station is communicating with a plurality of base stations.

B¹
15. (Original) The method according to claim 14 wherein the second rate is faster than the first rate
